

Product Information

AVENO Mineral Turbo 20W-50

0002-000003



Description

AVENO Mineral Turbo 20W-50 is a mineral multi-grade engine oil for gasoline and diesel car engines with or without turbocharging and commercial vehicle engines. Facilitates extended oil change intervals as per manufacturer's instructions. AVENO Mineral Turbo 20W-50 is characterized by its good cold starting properties, minimization of fuel consumption, friction and wear. With AVENO Mineral Turbo 20W-50, a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Mineral Turbo 20W-50 is an engine oil for year-round use, and is suitable for gasoline and diesel car engines and commercial vehicle engines. AVENO Mineral Turbo 20W-50 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API CH-4
- API SL/CF
- ACEA A3/B4
- ACEA E2

Recommendation

- Cummins CES 20071
- Deutz DQC II-10
- Mack EO-M
- MAN 271
- MB 228.1, MB 229.1
- MTU Type 1
- Volvo VDS
- VW 501 01/VW 505 00

Properties

- Neutrality towards sealants
- Suitable for catalytic converters
- A very good shear stability
- Prevention of black sludge formation
- A high oxidation stability
- Good cold starting properties, even at low temperatures
- A stable and excellent viscosity behaviour
- Good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	164,0	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	18,8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	129		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -15°C	8660	mpa*s	ASTM D 5293:2020
Density at 15°C	890	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015
Total Base Number (TBN)	11,0	mgkoh/g	ASTM D 2896:2015