# **Product Information**

## **AVENO SL Extra 5W-30**

0002-000476



#### Description

AVENO SL Extra 5W-30 is a synthetic smooth-running engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. It is characterized by excellent cold start properties, minimization of Fuel consumption, friction and wear. Extended oil change intervals according to manufacturer's instructions.

#### Instructions for use

AVENO SL Extra 5W-30 is ideally suited for energy-saving year-round use in modern petrol and diesel engines. The operating regulations of the motor vehicle and engine manufacturers are to be observed.

Quality classification		
Specification		
• API SL/CF	• ACEA A5/B5	
Recommendation		
<ul><li>Renault RN0700</li><li>VWC 53036</li></ul>	• Ford WSS-M2C913-C/-D	

### **Properties**

- Fuel saving under all operating conditions
- Very good detergent and dispersing properties
- Neutrality to sealing materials
- Low evaporation tendency, thus low oil consumption
- An extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources
- Excellent cold-start properties even at low temperatures

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	58,5	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	10,0	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	159		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Viscosity CCS at -30°C	5270	mpa*s	ASTM D 5293:2020	
Density at 15°C	855	kg/m³	DIN EN ISO 12185:1997-11	
Flash Point (COC)	236	celsius	DIN EN ISO 2592:2018-01	
Pour Point	-39	°C	ASTM D 7346:2015	
Total Base Number (TBN)	10,0	mgkoh/g	ASTM D 2896:2015	