

Product Information

AVENO DXS Premium 5W-30

0002-000541



Description

AVENO DXS Premium 5W-30 is a fully synthetic Mid SAPS smooth-running engine oil for petrol car engines with or without turbocharging and direct injection. AVENO DXS 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

AVENO DXS Premium 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol car engines. According to dexos1™ Gen3 specification it is recommended for General Motors under all operating conditions. The operating instructions of the car and engine manufacturers must be observed.

Quality classification

Specification

- API SN Plus (RC)
- API SP (RC)
- ILSAC GF-5/GF-6A

Approval

- API SN Plus
- API SP (RC)
- dexos1™ Gen3 (D335AADH374)
- ILSAC GF-6A

Recommendation

- Chrysler MS-6395
- Fiat 9.55535-CR1
- GM 6094M
- VWC 53034
- Ford WSS-M2C929-A, Ford WSS-M2C946-A/-B1
- Ford WSS-M2C961-A
- Opel/Vauxhall OV0401547-G30

Properties

- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Excellent protection against wear, corrosion and foaming
- High oxidation stability
- Excellent cold starting properties
- Fuel savings under all operating conditions
- Neutrality towards sealants
- Suitable for catalytic converters
- A secure lubricant film at very high operating temperatures

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	60,1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	10,8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	172		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -30°C	4100	mpa*s	ASTM D 5293:2020
Density at 15°C	846	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015
Total Base Number (TBN)	7,1	mgkoh/g	ASTM D 2896:2015