

Product Information

AVENO SEMiS 5W-30

0002-000026



Description

AVENO SEMiS 5W-30 is a semi-synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Facilitates extended oil change intervals as per manufacturer's instructions. AVENO SEMiS 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. With AVENO SEMiS 5W-30 a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO SEMiS 5W-30 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. AVENO SEMiS 5W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL/CF
- ACEA A3/B4

Recommendation

- BMW Longlife-01, BMW Longlife-98
- MB 229.3, MB 229.5
- RN0700/RN0710
- VW 502 00/505 00

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Excellent cold starting properties, even at low temperatures below -25°
- A very stable and excellent viscosity behavior and shear stability
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|--------------------------|
| Kinematic Viscosity at 40°C | 73.1 | mm ² /s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 12.3 | mm ² /s | DIN 51659-2:2017-02 |
| Viscosity Index | 167 | | DIN ISO 2909:2004-08 |
| Appearance | YELLOWBROWN | | VISUELL |
| Density at 15°C | 852 | kg/m ³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -39 | °C | ASTM D 7346:2015 |