

# Product Information

## AVENO ATF DX VI

0002-000185



### Description

AVENO ATF DX VI is an automatic gear oil on a basis of the latest technology of HC/HT hydrocrack oils, which is permitted by General Motors for use in vehicles with automatic gearboxes. The special formulation ensures a lifespan that is twice as long as that of a comparable ATF oil. AVENO ATF DX VI meets the requirements of the gear oil specifications of General Motors for all vehicles with hydramatic automatic gearboxes from 2006 onwards.

### Instructions for use

AVENO ATF DX VI is fully backward compatible with DEXRON®-III (H), III and II E applications. Always follow the recommendations in your vehicle's instruction manual.

### Quality classification

#### Specification

- Aisin Warner AW-1
- GM Dexron® VI
- GM Dexron LV

#### Recommendation

- Allison C4
- ATF Type 3.0, ATF Type 3.1
- BMW/Mini ATF 3+
- Chrysler MS-9602 ATF +4
- Ford MERCON® LV
- Ford WSS-M2C938-A
- Ford/Lincoln/Mercury XT-6-DSP [SP]
- Ford/Lincoln/Mercury XT-6-QSP [SP]
- Honda ATF DW-1
- Hyundai/Kia NWS-9638 T-5
- Jaguar/Land Rover Fluid 8432
- Mazda FZ, Mazda FW 6A EL, Mazda FW 6AX EL
- Isuzu ATF WSI
- MB 236.12, MB 236.14, MB 236.41
- Mitsubishi DiaQueen ATF J3/PA
- Nissan Matic-S
- Porsche 000 043 304 00
- Shell 3353, Shell 134, Shell M-1375.4, Shell 12108
- SP-IV/SPH-IV/SP-IV-RR
- Toyota JWS 3324, Toyota/Scion FZ
- VOLVO 97342 (AT 102)
- VW G 052 533, VW G 055 005 A/A2
- VW G 055 540 A2, VW G 060 162 A1/A2/A6
- ZF LifeguardFluid 5/6

### Properties

- Superior wear protection
- Better resistance to foaming for smooth switching
- Reduced wear of bearings, bushings and gears
- Longer change intervals
- Excellent fluidity at low temperatures
- Good resistance against lubricant failures under hard operating conditions
- Outstanding resistance to oil sludge and deposit formation
- Longer oil lifespan, extension of the gearbox lifespan
- Prevention of coupling grinding in modulation rotary converters

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	29.1	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	6.0	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	161		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	841	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015