

# Product Information

## AVENO CVT Fluid GREEN

0002-000406



### Description

AVENO CVT Fluid is a latest generation automatic gearbox lubricant for CVT automatic gearboxes. AVENO CVT Fluid guarantees optimum power transmission. AVENO CVT Fluid is designed on a basis of synthetic oils with special additives and inhibition, which guarantee the flawless function of the automatic gearbox.

### Instructions for use

AVENO CVT Fluid was developed for use in CVT automatic gearboxes (belt CVTs and chain CVT). AVENO CVT Fluid ensures a stable viscosity, even under the highest mechanical stresses in the transmission elements (push belt). \*Use in Honda CVT (HMMF) with starting clutch is not recommended.

### Recommendation

- Audi TL 52 180, Audi TL 52 516
- BMW/Mini EZL 799
- Chrysler/Dodge/Jeep CVTF+4
- Chrysler/Dodge/Jeep NS-2
- Daihatsu TC, Daihatsu Amix CVTF-DC/CVTF-DFE
- Ford CVT23/30, Ford MERCON® C
- GM/Saturn DEX-CVT
- Honda HCF-2, Honda HMMF
- Hyundai/Kia CVTF
- MB 236.20
- Mitsubishi CVTF-Diaqueen J-1/J-4
- Mitsubishi Diaqueen NS-2
- Nissan NS-2/NS-3
- Renault ELFMATIC
- Subaru ECVT/iCVT
- Subaru NS-2, Subaru Lineartronic CVTF
- Suzuki CVT Fluid Green 1/Green 2
- Suzuki NS-2, Suzuki TC
- Toyota TC

### Properties

- Very high and stable viscosity index
- Very low pour point
- Very good oxidation stability
- Well coordinated friction properties
- Very good lubrication properties, even at low temperatures
- Most extensive protection against wear, corrosion and foaming
- Neutral behaviour towards sealing agents
- Neutral behaviour towards non-ferrous metals due to inhibition

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	33.2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7.2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	189		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Density at 15°C	844	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015