

Product Information

AVENO ATF 6HP

0002-000685



Description

AVENO ATF 6HP is a synthetic gear oil based on high-quality hydrocrack oils with a special additive and inhibition, which ensure the perfect functioning of the automatic transmission. It is an ATF (Automatic Transmission Fluid) of the latest generation for all 6-speed automatic transmissions from ZF. Guarantees maximum wear protection in every operating condition. It can be used as a replacement for ZF-LIFEGUARDFLUID 6 (ZF No.S671 090 255) outside the warranty period.

Instructions for use

AVENO ATF 6HP was developed for use in the latest 6 HP series transmissions of ZF: 6HP19, 6HP19A, 6HP19X (not for Audi Q7), 6HP21, 6HP21X, 6HP26, 6HP26X, 6HP26A61 (not on Audi W12 engine), 6HP28, 6HP28X, 6HP28A61, 6HP32, 6HP32A, 6HP32X.

Recommendation

- AML 4G4319A509/AA/S
- Audi/VW G 055 005 A1/A2/A6
- Bentley PY112995PA
- BMW 83 22 0 142 516
- BMW 83 22 2 305 396
- Hyundai/Kia 040000C90SG
- Jaguar C2C 8432
- Land Rover TYK500050
- Maserati 231603
- Volvo 97342 (AT 102)

Properties

- High and stable viscosity index
- Very good oxidation stability
- High thermal and oxidative stability
- Excellent cooling capacity
- Reliable protection against wear, corrosion and foaming
- Good lubrication properties, even at low temperatures in winter
- Coordinated friction properties

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	30.5	mm ² /s	DIN ISO 51562-2:1988-12
Kinematic Viscosity at 100°C	6.2	mm ² /s	DIN ISO 51562-2:1988-12
Viscosity Index	152		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	849	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015